



Note: Images shown may include optional features.

## Base Boat Specifications

Length	20 ft.	6.10 m
L.O.A.	22 ft.	6.71 m
Beam	96 in.	2.44 m
Height of Sides	34 in.	86.36 cm
Chine Width	68 in.	1.73 m
Fuel Capacity	42 USG	159 L
Maximum HP	225 HP	
Motor Length	25 in.	63.50 cm
Hull Deadrise	16 Degrees	
Side Thickness	0.125" / 5052 Aluminum Alloy	
Bottom Thickness	0.190" / 5086 Aluminum Alloy	
Transom Thickness	0.250" / 5052 Aluminum Alloy	

## Standard Hull Features

One Piece Hull Sides w/ Wide Wraparound Seamless Gunnels  
One Piece Bottom  
Full Length Engineered Box Stringers  
(2) Full Length Formed-In External Hull Stiffeners  
Exclusive Tri-Structure Full Length Reverse Chine  
(2) Performance Lifting Strakes  
Fully Welded Heavy Duty Keel Guard  
Welded Thru-Hull Fittings  
(5) Welded 8" Cleats  
Welded Heavy Duty Bow & Transom Eyes  
Welded 4" Bow Rails  
Double Walled Self-Draining Drop Bow  
Large Fully Welded Bow Drains  
Welded Fully Width Transom Platform w/ Undermount 3-Step Telescoping Ladder  
Welded External Motor Bracket  
Transom Fish Box w/ (2) HDPE Material Doors  
Transducer Mounting Bracket

## Windshield Features

Welded 5 Piece Walk-Thru Windshield  
Heavy Duty External Set 1/4" Safety Glass Windows  
Lexan Shatter Proof Hinged Center Window  
Welded High Mount Windshield Grab Rails  
Pantographic Self-Parking Driver Side Windshield Wiper

## Standard Interior Features

(2) Seats on Pedestals w/ Slide & Swivel  
(2) 36" Storage Box Bench Seats w/ Removable Backrests  
Open Glove Box  
Sport Steering Wheel  
No Feedback Single Cable Steering System  
Locking Floor Storage Compartment  
(2) Locking Interior Transom Access Doors  
Bow Step w/ Non-skid Surface and Netted Storage  
(2) Full Length Welded Side Storage Trays  
(6) Cup Holders  
Premium Marine Vinyl Decking  
Vinyl Wrapped Transom and Console Kick Boards  
(2) Under Console Storage Trays  
Welded Passenger Grab Rail

## Standard Electrical Features

Analog Fuel Gauge  
Premium Switch Panel  
Electric Horn  
12V Power Point  
Premium Marine Wiring Harness w/ Water Tight Connections  
Safety Hub Power Distribution Block  
LED Navigation Lights Package  
Under Dash & Transom Courtesy LED Lights  
Electric Bilge Pump w/ Auto Float Switch  
Conduit Under Bow Deck for Running Wiring

## Standard Color & Graphics

Speckle Painted Bow, Dash, Windshield, and Interior Side Walls  
Vinyl Side Logo

## Optional Trailer

EZ Loader 4000lbs. Galvanized Tandem Axle Bunk Trailer  
Includes: Spring Suspension; (2) Carpeted Bunks w/ Slick Bunk Caps; Plastic Fenders w/ Non-Skid Steps; Tongue Jack; 14" Wheels; Hydraulic Surge Disc Brakes