

2400 OLYMPIA



Note: Images shown may include optional features/cabins.

Base Boat Specifications

Length	24 ft.	7.32 m
L.O.A.	26 ft.	7.92 m
Beam	108 in.	2.74 m
Height of Sides	40 in.	1.02 m
Chine Width	90 in.	2.13 m
Cabin Length	80 in.	2.03 m
Cockpit Length	83 in.	2.11 m
Fuel Capacity	73 USG	276 L
Maximum HP	400 HP	
Motor Length	25 in.	63.50 cm
Hull Deadrise	Progressive 18 Degrees	
Side Thickness	0.160" / 5052 Aluminum Alloy	
Bottom Thickness	0.250" / 5086 Aluminum Alloy	
Transom Thickness	0.250" / 5052 Aluminum Alloy	

Standard Hull Features

One Piece Hull Sides w/ Wide Wraparound Seamless Gunnels
One Piece Bottom
Full Length Engineered Box Stringers
(4) Full Length Formed-In External Hull Stiffeners
Exclusive Tri-Structure Full Length Reverse Chine
(4) Performance Lifting Strakes
Fully Welded Heavy Duty Keel Guard
Welded Thru-Hull Fittings
(7) Welded 8" Cleats
Welded Heavy Duty Bow & Transom Eyes
Welded 1" Diameter High Bow Rails
Self-Bailing Aluminum Cockpit Flooring w/ Non-skid Surface
Upswept Bow
Welded Bow Pulpit w/ Anchor Roller
Self-Draining Anchor/Rope Locker w/ Interior Hatch
Welded Full Width Transom Platform
Welded 4" Stern Rails
(2) Welded Downrigger Mounting Pads
Transom Fish Locker w/ HDPE Material Door
3-Step Telescoping Ladder w/ Grab Handle
Starboard Transom Door
Port Side Net Holder

Windshield / Window Features

Forward Sloping 2 Piece Windshield w/ ¼" Safety Glass
(2) Self-Parking Windshield Wipers
Aluminum Framed Clamp-in Style Windows w/ ¼" Safety Glass
Marine Grade Aluminum Framed Weathertight Door w/ Window

Standard Interior Features

(2) Fully Adjustable Spring Ride Suspension Seats
(2) Storage Box Bench Seats w/ Removable Backrests
Locking Glove Box
Hydraulic Steering w/ Tilt Helm
Stainless Steel Rubber Coated Steering Wheel
Welded Passenger Grab Rail
Floor Fish Locker w/ Macerator Pump
(2) Locking Interior Transom Access Hatches
(4) 5" Welded Cockpit Side Storage Trays
Full Marine Carpeted Sound Dampening Side Walls
Offshore Deck Hatch w/ Screen
LED Interior Lighting
Built in Overhead Grab Rails
Upholstered Finished Cuddy Cabin w/ Cushions
V-berth Lights
V-berth Privacy Enclosure
V-berth Storage
Raw Water Washdown w/ Hose Receptacle

Standard Electrical Features

Analog Tach, Fuel, Trim & Volt Dash Instrumentation
Premium Switch Panel
Electric Horn
12V Power Point
Premium Marine Wiring Harness w/ Water Tight Connections
Safety Hub Power Distribution Block
Transom Battery Tray
4-Way Selector Battery Switch
LED Navigation Lights Package
Under Dash & Transom Courtesy LED Lights
LED Cockpit Flood Light
(2) Bilge Pumps w/ Auto Float Switch (1250 & 2200 GPH)
9 x 12 Trim Tabs

Standard Color & Graphics

1/3 Hull Side and Roof Paint
2 Tone (Color and Speckle) Cabin Side
Speckle Painted gunnels and Transom
Raised Dome Vinyl Side Logo

Optional Trailer

EZ Loader 8500lbs. Capacity Galvanized Tandem Axle Bunk
Trailer Includes: Torsion Axle Suspension; Adjustable Frame
Construction; Dual Bunks w/ Bunk Skids; Fenders w/ Extra
Large Non-Skid Steps; Tongue Jack; 16" Wheels; Electric
Drum Brakes