

# 2600 OLYMPIA



Note: Images shown may include optional features/cabins.

## Base Boat Specifications

Length	26 ft.	7.92 m
L.O.A.	28 ft.	8.53 m
Beam	108 in.	2.74 m
Height of Sides	40 in.	1.02 m
Chine Width	90 in.	2.13 m
Cabin Length	116 in.	2.95 m
Cockpit Length	71 in.	1.80 m
Fuel Capacity	110 USG	416 L
Maximum HP	600 HP	
Motor Length	25 in.	63.50 cm
Hull Deadrise	Progressive 18 Degrees	
Side Thickness	0.160" / 5052 Aluminum Alloy	
Bottom Thickness	0.250" / 5086 Aluminum Alloy	
Transom Thickness	0.250" / 5052 Aluminum Alloy	

## Standard Hull Features

One Piece Hull Sides w/ Wide Wraparound Seamless Gunnels  
Full Length Engineered Box Stringers  
(4) Full Length Formed-In External Hull Stiffeners  
Exclusive Tri-Structure Full Length Reverse Chine  
Performance Lifting Strakes  
Fully Welded Heavy Duty Keel Guard  
Welded Thru-Hull Fittings  
(7) Welded 8" Cleats  
Welded Heavy Duty Bow & Transom Eyes  
Welded 1" Diameter High Bow Rails  
Self-Bailing Aluminum Cockpit Flooring w/ Non-skid Surface  
Upswept Bow  
Welded Bow Pulpit w/ Anchor Roller  
Self-Bailing Anchor/Rope Locker w/ Interior Hatch  
Welded Full Width Transom Platform  
4" Welded Stern Rails  
(2) Welded Downrigger Mounting Pads  
Transom Fish Locker w/ HDPE Material Door  
3-Step Telescoping Ladder w/ Grab Handle  
Starboard Transom Door  
Port Side Net Holder

## Windshield / Window Features

Forward Sloping 2 Piece Windshield w/ ¼" Safety Glass  
(2) Self-Parking Windshield Wipers  
Aluminum Framed Clamp-in Style Windows w/ ¼" Safety Glass  
Marine Grade Aluminum Framed Weathertight Door w/ Window

## Standard Interior Features

(2) Fully Adjustable Spring Ride Suspension Seats  
(2) Storage Box Bench Seats w/ Removable Backrests  
Locking Glove Box  
Hydraulic Steering w/ Tilt Helm  
Stainless Steel Rubber Coated Steering Wheel  
Welded Passenger Grab Rail  
Floor Fish Locker w/ Macerator Pump  
(2) Locking Interior Transom Access Hatches  
(4) 5" Welded Cockpit Side Storage Trays  
(4) Cup Holders  
Full Marine Carpeted Sound Dampening Side Walls  
Offshore Deck Hatch w/ Screen  
LED Interior Lighting  
Built in Overhead Grab Rails  
Upholstered Finished Cuddy Cabin w/ Cushions  
V-berth Lights  
V-berth Privacy Enclosure  
V-berth Storage  
Welded Stand-up Interior Head w/ Pump-out Toilet & Macerator  
Raw Water Washdown w/ Hose Receptacle

## Standard Electrical Features

Analog Tach, Fuel, Trim & Volt Dash Instrumentation  
Premium Switch Panel  
Electric Horn  
12V Power Point  
Premium Marine Wiring Harness w/ Water Tight Connections  
Safety Hub Power Distribution Block  
Transom Battery Tray  
4-Way Selector Battery Switch  
LED Navigation Lights Package  
Under Dash & Transom Courtesy Lights  
LED Cockpit Flood Light  
(2) Bilge Pumps w/ Auto Float Switch (1250 & 2200 GPH)  
9 x 12 Trim Tabs

## Standard Color & Graphics

1/3 Hull Side and Roof Paint  
2 Tone (Color and Speckle) Cabin Side  
Speckle Painted gunnels and Transom  
Raised Dome Vinyl Side Logo

## Optional Trailer

EZ Loader 8500lbs. Capacity Galvanized Tandem Axle Bunk  
Trailer Includes: Torsion Axle Suspension; Adjustable Frame Construction; Dual Bunks w/ Bunk Skids; Fenders w/ Extra Large Non-Skid Steps; Tongue Jack; 16" Wheels; Electric Drum Brakes