





Note: Images shown may include optional features/cabins.

Base Boat Specifications

•		
Length	28 ft.	8.53 m
L.O.A.	30 ft.	9.14 m
Beam	108 in.	2.74 m
Height of Sides	40 in.	1.02 m
Chine Width	90 in.	2.13 m
Cabin Length	116 in.	2.95 m
Cockpit Length	95 in.	2.41 m
Fuel Capacity	110 USG	416 L
	700 110	

Maximum HP 700 HP

Motor Length 25 in. 63.50 cm Hull Deadrise Progressive 18 Degrees

Side Thickness 0.160" / 5052 Aluminum Alloy
Bottom Thickness 0.250" / 5086 Aluminum Alloy
Transom Thickness 0.250" / 5052 Aluminum Alloy

Standard Hull Features

One Piece Hull Sides w/ Wide Wraparound Seamless Gunnels Full Length Engineered Box Stringers

(4) Full Length Formed-In External Hull Stiffeners

Exclusive Tri-Structure Full Length Reverse Chine

Performance Lifting Strakes

Fully Welded Heavy Duty Keel Guard

Welded Thru-Hull Fittings

(7) Welded 8" Cleats

Welded Heavy Duty Bow & Transom Eyes

Welded 1" Diameter 18" High Bow Rails

Self-Bailing Aluminum Cockpit Flooring w/ Non-skid Surface Upswept Bow

Welded Bow Pulpit w/ Anchor Roller

Self-Bailing Anchor/Rope Locker w/ Exterior Hatch

Welded Full Width Transom Platform

4" Welded Stern Rails

(2) Welded Downrigger Mounting Pads

Transom Fish Locker w/ HDPE Material Door

3-Step Telescoping Ladder w/ Grab Handle

Starboard Transom Door

Port Side Net Holder

Windshield / Window Features

Forward Sloping 2 Piece Windshield w/ ¼" Safety Glass (2) Self-Parking Windshield Wipers

Aluminum Framed Clamp-in Style Windows w/ ¼" Safety Glass

Marine Grade Aluminum Framed Weathertight Door w/ Window

Standard Interior Features

(2) Fully Adjustable Spring Ride Suspension Seats

(2) Storage Box Bench Seats w/ Removable Backrests

Locking Glove Box w/ Radio Shelf

Hydraulic Steering w/ Tilt Helm

Stainless Steel Rubber Coated Steering Wheel

Welded Passenger Grab Rail

In Floor Fish Locker w/ Macerator Pump

(2) Locking Interior Transom Access Hatches

(4) 5" Welded Cockpit Side Storage Trays

(4) Cup Holders

Full Marine Carpeted Sound Dampening Side Walls

Offshore Deck Hatch w/ Screen

LED Interior Lighting

Built in Overhead Grab Rails

Upholstered Finished Cuddy Cabin w/ Cushions

V-berth Lights

V-berth Privacy Enclosure

V-berth Storage

Welded Stand-up Interior Head w/ Pump-out Toilet &

Macerator

Raw Water Washdown w/ Hose Receptacle

Standard Electrical Features

Analog Tach, Fuel, Trim & Volt Dash Instrumentation

Premium Switch Panel

Electric Horn

12V Power Point

Premium Marine Wiring Harness w/ Water Tight Connections

Safety Hub Power Distribution Block

Transom Battery Tray

4-Way Selector Battery Switch

LED Navigation Lights Package

Under Dash & Transom Courtesy LED Lights

LED Cockpit Flood Light

(2) Bilge Pumps w/ Auto Float Switch (1250 & 2200 GPH)

9 x 12 Trim Tabs

Standard Color & Graphics

1/3 Hull Side and Roof Paint

2 Tone (Color and Speckle) Cabin Side

Speckle Painted gunnels and Transom

Raised Dome Vinyl Side Logo

Optional Trailer

EZ Loader 12000lbs. Capacity Galvanized Triple Axle Bunk Trailer Includes: Torsion Axle Suspension; Adjustable Frame Construction; Dual Bunks w/ Bunk Skids; Fenders w/ Extra Large Non-Skid Steps; Tongue Jack; 15" Wheels; Electric Drum Brakes